


Features

- High efficiency 156mm poly crystalline cells
- High quality eva & back sheet to ensure high performance and provide good weather \ resistance for rugged environments.
- Anodized aluminum alloy frame and tempered & textured clear glass with low iron content to enhance high efficiency.
- Bypass diodes provided to avoid effect of partial shading.
- IEC61215, IEC61730 & IEC61701 certified
- An ISO 9001:2008 & ISO 14001:2004 certified production facility.
- PV module power rating from 3wp to 300wp
- 25 years limited warranty on power output. Output will be still 80% in 25 years, based on rated module performance less the negative tolerance.

Electrical Specifications:		
Product Description	SS-225	SS-235
Rated POWER Pmax - [W]	225	235
Rated Voltage Vmax - [V]	28.90	29.90
Rated Current Imax - [A]	7.80	7.90
Open Circuit Voltage Voc - [V]	37.00	37.00
Short Circuit Current Isc - [A]	8.40	8.40
Tolerance	±3%	±3%
Standard Test Conditions: Irradiance 1000 W/ m ² , Module temperature 25 °C, Spectrum AM 1.5		



Current voltage dependence on Irradiance and module temperature.
this is only indicative showing affect of temperature and intensity on power

Temperature Coefficients

Voltage Voc : (- 0.379% of Voc / C)
Current Isc : (- 0.0396% of Isc / C)
Power Pmax : (- 0.48%/deg C)

Maximum system voltage : 1000VDC
Operating Module Temperature :
-40°C to +90°C
NOCT : 47°C ± 2°C

Certifications




SIRIUS SOLAR ENERGY SYSTEMS Pvt.Ltd.

Regd.Office : H.No.:35-6-35/14, Plot No.:454, Vivekananda Nagar, Kukatpally, Hyd - 072

Phone: 040 - 23065133, Fax No: +91-40-23064121, Cell:+91-9705922258

Email : marketing@siriussolarenergy.com, Web Site: www.siriussolarenergy.com



Mechanical Specifications:	SS-225	SS-235
Length [mm] - A	1657± 1	1657 ± 1
Width [mm] - B	987 ± 1	987 ± 1
Thickness [mm] - C	50	50
Mounting slot [mm] - D	1145 mm	1145 mm
Mounting slot [mm] - E	951 mm	951 mm
Mounting hole (mm)	12X10	12X10
Earth hole	4mm dia	4mm dia
Aprox. weight [Kg]	18.5	18.5
No. of cells & Arrangement	60 (6X10)	60 (6X10)

Other Characteristics:	
Cell type	High Efficiency Multi Crystalline Cells (156mm X 156mm)
Front Glass	Toughened Textured Glass
Glass thickness	3.2 mm
Cell Encapsulation	EVA (Ethylene Vinyl Acetate)
Back sheet	Poly vinyl Fluoride
Frame	Silver Anodized Aluminum Alloy
Junction Box	4 rail junction box
No.of Diodes	3

specifications are subject to change without prior notice due to constant improvement in design & technology

SIRIUS SOLAR ENERGY SYSTEMS Pvt.Ltd.

Regd.Office : H.No.:35-6-35/14, Plot No.:454, Vivekananda Nagar, Kukatpally, Hyd - 072

Phone: 040 - 23065133, Fax No: +91-40-23064121, Cell:+91-9705922258

Email : marketing@siriussolarenergy.com, Web Site: www.siriussolarenergy.com