


Features

- High efficiency 156mm poly crystalline cells
- High quality eva & back sheet to ensure high performance and provide good weather \ resistance for rugged environments.
- Anodized aluminum alloy frame and tempered & textured clear glass with low iron content to enhance high efficiency.
- Bypass diodes provided to avoid effect of partial shading.
- IEC61215, IEC61730 & IEC61701 certified
- An ISO 9001:2008 & ISO 14001:2004 certified production facility.
- PV module power rating from 3wp to 300wp
- 25 years limited warranty on power output. Output will be still 80% in 25 years, based on rated module performance less the negative tolerance.

Electrical Specifications:			
Product Description	SSI-250	SS-280	SS-300
Rated Power Pmax - [W]	250	280	300
Rated Voltage Vmax - [V]	34.0	35.7	36.7
Rated Current Imax - [A]	7.50	8.30	8.20
Open Circuit Voltage Voc - [V]	44.0	45.0	45.0
Short Circuit Current Isc - [A]	8.30	8.53	8.60
Tolerance	±3%	±3%	±3%
Standard Test Conditions: Irradiance 1000 W/ m ² , Module temperature 25 °C, Spectrum AM 1.5			



Current voltage dependence on Irradiance and module temperature.
this is only indicative showing affect of temperature and intensity on power

Temperature Coefficients

Voltage Voc : (- 0.379% of Voc / C)
Current Isc : (- 0.0396% of Isc / C)
Power Pmax : (- 0.48%/deg C)

Maximum system voltage : 1000VDC
Operating Module Temperature :
-40°C to +90°C
NOCT : 47°C ± 2°C

Certifications



SIRIUS SOLAR ENERGY SYSTEMS Pvt.Ltd.

Regd.Office : H.No.:35-6-35/14, Plot No.:454, Vivekananda Nagar, Kukatpally, Hyd - 072

Phone: 040 - 23065133, Fax No: +91-40-23064121, Cell:+91-9705922258


Email : marketing@siriussolarenergy.com, Web Site: www.siriussolarenergy.com



SIRIUS

Solar Energy Systems
An ISO 9001:14001 COMPANY

Module Drawing & Mounting details:



Mechanical Specifications:	SSI-250	SS-280	SS-300
Length [mm] - A	1986 ± 1	1986 ± 1	1986 ± 1
Width [mm] - B	993 ± 1	993 ± 1	993 ± 1
Thickness [mm] - C	50	50	50
Mounting slot [mm] - D	1302mm	1302	1302
Mounting slot [mm] - E	945 mm	945	945
Mounting hole (mm)	10X12 mm	10X12	10X12
Earth hole	4mm dia	4mm dia	4mm dia
Aprox. weight [Kg]	23	23	23
No. of cells & Arrangement	72 (6X12)	72 (6X12)	72 (6X12)

Other Characteristics:

Cell type	High Efficiency Multi Crystalline Cells (156mm X 156mm)
Front Glass	Toughened Textured Glass
Glass thickness	4.0 mm
Cell Encapsulation	EVA (Ethylene Vinyl Acetate)
Back sheet	Poly vinyl Fluoride
Frame	Silver Anodized Aluminum Alloy
Junction Box	4 rail junction box
No.of Diodes	3

specifications are subject to change without prior notice due to constant improvement in design & technology

SIRIUS SOLAR ENERGY SYSTEMS Pvt.Ltd.

Regd.Office : H.No.:35-6-35/14, Plot No.:454, Vivekananda Nagar, Kukatpally, Hyd - 072

Phone: 040 - 23065133, Fax No: +91-40-23064121, Cell:+91-9705922258

Email : marketing@siriussolarenergy.com, Web Site: www.siriussolarenergy.com